



**UNIDADES INTERIORES**

RAV-RM561BTP-E  
RAV-RM801BTP-E  
RAV-RM1101BTP-E  
RAV-RM1401BTP-E



**UNIDADES EXTERIORES**

RAV-GP561ATP-E      RAV-GP801AT-E      RAV-GP1101AT(8)-E  
RAV-GP1401AT(8)-E  
RAV-GP1601AT(8)-E



**CONTROLES REMOTOS**

TCB-AX32E2      RBC-AMS55E-ES(EN)  
RBC-ASC11E  
RBC-AMT32E  
RBC-AS41E



SCOP MÁX.



**4,81**

CAPACIDAD



**5kW > 14kW**

FUNCIONAMIENTO



**-27°C > +52°C**

**SPA SDI TRIFÁSICA**

**SUPER DIGITAL INVERTER**

Nombre Comercial		Spa SDI Trifásica 110	Spa SDI Trifásica 140	Spa SDI Trifásica 160	
<b>Capacidad de refrigeración</b>	kW	10,0	12,5	14,0	
Rango de refrigeración (Mín. - Máx.)	kW	2,6 - 12,0	2,6 - 14,0	2,6 - 16,0	
Consumo Nom. <Mín. - Máx.>	kW	2,6 <0,7 - 4,0>	3,8 <0,7 - 4,9>	4,5 <0,7 - 6,5>	
EER	kW/kW	3,87	3,28	3,12	
SEER	kW/kW	5,70	5,48	5,36	
Clase Energética		A+	-	-	
Consumo estacional anual	kWh/año	613	-	-	
<b>Capacidad de calefacción</b>	kW	11,2	14,0	16,0	
Rango de calefacción (Mín. - Máx.)	kW	2,4 - 15,6	2,4 - 18,0	2,4 - 19,0	
Consumo Nom. <Mín. - Máx.>	kW	2,8 <0,5 - 4,4>	3,7 <0,5 - 5,7>	4,6 <0,5 - 7,0>	
COP	kW/kW	4,06	3,83	3,50	
SCOP	kW/kW	4,14	3,95	3,93	
Clase Energética		A+	-	-	
Consumo estacional anual	kWh/año	3.644	-	-	
<b>Unidad Interior</b>		<b>RAV-RM1101BTP-E</b>	<b>RAV-RM1401BTP-E</b>	<b>RAV-RM1601BTP-E</b>	
Caudal de aire (A/B)	m³/h - l/s	2.100/1.500 - 583/417	2.100/1.500 - 583/417	2.100/1.500 - 583/417	
Presión sonora (A/M/B)	dB(A)	40/36/33	40/36/33	40/36/33	
Potencia sonora (A/M/B)	dB(A)	63/58/54	63/58/54	63/58/54	
Dimensiones (Alt. x Anch. x Prof.)	mm	275 x 1.400 x 750	275 x 1.400 x 750	275 x 1.400 x 750	
Peso	kg	40	40	40	
Presión estática externa Fáb. <Mín. - Máx.>	Pa	50 <30 - 120>	50 <30 - 120>	50 <30 - 120>	
<b>Unidad Exterior</b>		<b>RAV-GP1101AT8-E</b>	<b>RAV-GP1401AT8-E</b>	<b>RAV-GP1601AT8-E</b>	
Caudal de aire	m³/h - l/s	6.060 - 1.683	6.180 - 1.717	6.180 - 1.717	
Presión sonora Ref / Cal	dB(A)	49 / 50	51 / 52	51 / 53	
Dimensiones (Alt. x Anch. x Prof.)	mm	1.340 x 900 x 320	1.340 x 900 x 320	1.340 x 900 x 320	
Peso	kg	95	95	95	
Máxima corriente en arranque (MCA)	A	16,2	16,5	16,9	
Conexiones (Gas / Líquido)	pulgadas	5/8" - 3/8"	5/8" - 3/8"	5/8" - 3/8"	
Longitud de tuberías Nom. <Mín. - Máx.>	m	7,5 <3 - 75>	7,5 <3 - 75>	7,5 <3 - 75>	
Diferencia máxima de altura	m	30	30	30	
Longitud de tubería precargada	m	30	30	30	
Carga adicional	g/m	40	40	40	
Rango de operación (Refrigeración/Calefacción)	°C	-15 ~ 52 / -27 ~ 15	-15 ~ 52 / -27 ~ 15	-15 ~ 52 / -27 ~ 15	
Refrigerante	kg	2,6	2,6	2,6	
<b>Precio de lista</b>	Unidad Interior	€	<b>988</b>	<b>1.048</b>	<b>1.225</b>
	Unidad Exterior	€	<b>2.684</b>	<b>3.398</b>	<b>3.750</b>
	Mando (RBC-ASC11E)	€	<b>68</b>	<b>68</b>	<b>68</b>
	Conjunto	€	<b>3.740</b>	<b>4.514</b>	<b>5.043</b>