



Ficha técnica

SPLIT MURAL Q6



MODELO	SKY-S026Q6R32		SKY-S035Q6R32		SKY-S052Q6R32		SKY-S071Q6R32	
	INT.	EXT.	INT.	EXT.	INT.	EXT.	INT.	EXT.
Alimentación eléctrica / Conexión	V, F, HZ		220-240V		(1 Fase~ 50Hz) / Unidad exterior			
RENDIMIENTO								
Capacidad refrigeración	Capacidad (min. - max.)	W	2.500 (400 – 2.900)	3.400 (550 – 3.900)	5.270 (1.000 – 6.700)	6.450 (1.400 – 7.000)		
	Consumo (min.-max.)	W	750 (150 – 1.430)	1.020 (180 – 1.560)	1.540 (320 – 2.460)	1.840 (380 – 2.800)		
	Corriente	A	3,3	4,5	7	8,9		
	SEER	-	6,1	6,1	6,3	6,4		
Capacidad calefacción	Capacidad (min. - max.)	kW	2.800 (400 – 3.300)	3.600 (600 – 4.200)	5.500 (1.100 – 6.800)	6.600 (1.500 – 7.900)		
	Consumo (min.-max.)	W	775 (135 – 1.550)	995 (140 – 1.650)	1.480 (350 – 2.300)	1.750 (400 – 2.500)		
	Corriente	A	3,4	4,4	6,3	8,4		
	SCOP	-	5,1	5,1	5,4	5,1		
Clasificación energética	Calor	A+++	A+++	A+++	A+++			
CARACTERÍSTICAS								
Unidad interior	Potencia sonora	dB(A)	54/39/36/30	55/40/37/31	58/55/42/40	61/57/48/46		
	Presión sonora	dB(A)	40/36/24/19	41/37/25/20	47/44/31/29	48/44/35/33		
	Caudal de aire	m3/h	520/440/230/150	550/470/250/180	850/760/570/480	1.090/930/670/560		
	Rango de temperatura seleccionable	°C	16 ~ 31	16 ~ 31	16 ~ 31	16 ~ 31		
Unidad exterior	Potencia sonora	dB(A)	61	62	63	68		
	Presión sonora	dB(A)	52	53	55	59		
	Caudal de aire	m3/h	1.800	1.800	2.800	3.300		
	Temperatura de operación frío/calor	°C	(-15 ~ 43) / (-15 ~ 24)	(-15 ~ 43) / (-15 ~ 24)	(-15 ~ 43) / (-15 ~ 24)	(-15 ~ 43) / (-15 ~ 24)		
Refrigerante	Compresor		Sanyo	Sanyo	Panasonic	Panasonic		
	Tipo / Carga	R32/Kg	R32/0,5	R32/0,7	R32/0,9	R32/1		
	Carga adicional >5	g/m	16	16	16	40		
Presión de diseño		Mpa	4,3/2,5	4,3/2,5	4,3/2,5	4,3/2,5		
Perímetro climatizable (dependiendo de las condiciones de la habitación)		m2	18	23	40	50		
DIMENSIONES Y PESO								
Unidad interior	Dimensiones netas (An×Al×Pr)	mm	792x279x195	792x279x195	972x302x224	1.081x327x248		
	Peso neto	Kg	9	9	13	16		
Unidad exterior	Dimensiones netas (An×Al×Pr)	mm	830x540x325	830x540x325	890x598x372	960x700x396		
	Peso neto	Kg	27	29	40	43,5		
CONEXIONES								
Tubería frigorífica	Líquido - Gas	Pulg.	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 5/8"		
	Longitud max.	m	20	20	25	25		
	Desnivel max.	m	10	10	10	10		
Conexiones eléctricas	Alimentación	mm	2 + T x 2,5	2 + T x 2,5	2 + T x 2,5	2 + T x 2,5		
	Interconexión	mm	3 + T x 2,5	3 + T x 2,5	3 + T x 2,5	3 + T x 2,5		
CÓDIGO EAN	Conjunto		8435483815834	8435483815841	8435483815827	8435483815810		